

Evolution

for your Demand



CPD505

8CH MPEG-4 Network DVR

COST & PERFORMANCE

» Features

MPEG-4 real time compression format

Extensive recording time by connected to Independent Disk Array.

Remote surveillance on mobile phone via 3G/GPRS, or on PC through internet connection

Easy file backup methods with USB flash memory, AP, DVD R/W (optional), and CD R/W (optional)

Alarm trigger recording will send alert with images to designated e-mail and FTP address. Also support pre-alarm recording

Advanced motion detection function and convenient search function.

Pentaplex function (live display, recording, playback, backup and network)

Web function supports MJPEG compression format for transmitting over the internet

Remote **E**vent **T**rigger **R**ecording.

Web surveillance supports multiple viewers simultaneously

Support covert screen for live view channels

IR remote control of the system and PTZ through RS-485

Support PELCO-D protocol

Hot point to control the PTZ.

2 HDD bases built-in, each can support more than 400GB

Easy system upgrade via USB

Support TCP/IP, PPPoE, DHCP and DDNS function

Support manual / timer / motion / alarm / remote recording functions

Record audio with 4CH in and 2CH out

System auto recovery after power reconnected

Watermark function ensures authentication of recorded images

Optional: DVD R/W / CD R/W backup; Independent disk array; VGA output



Evolution for your Demand

Tel: 886-2-2655-3866

www.cpcamcctv.com

Fax: 886-2-2655-3855

marketing@cpcamcctv.com



CPD505

8CH MPEG-4 Real time Network DVR

Specifications

MODEL	CPD505
Video System	NTSC/ PAL (switch able)
Video Compression Format	MPEG-4
Video Input	8 Channels. Composite video signal 1 Vp-p 75 BNC
Video Loop Out	8 Channels. Composite video signal 1 Vp-p 75 BNC
Video Output	Main Monitor Output : Composite video signal 1 Vp-p 75 BNC Call Monitor Output : Composite video signal 1 Vp-p 75 BNC
Maximum Recording Rate	Frame: 720 x 480 pixels with 60 IPS NTSC / 720 x 576 pixels with 50 IPS PAL CIF: 352 x 240 pixel 240 IPS NTSC / 352 x 288 pixels with 200 IPS PAL
Adjustable Recording Speed	Frame: 60, 30, 15, 7 IPS <NTSC>/ 50, 25, 12, 6 IPS <PAL> CIF: 240, 120, 60, 30 IPS <NTSC>/ 200, 100, 50, 25 IPS <PAL>
Image Quality Setting	Best, High, Normal, and Basic
Hard Disk Storage	IDE type, ATA66, supported HDD x 2, support each HDD capacity over 400GB
HDD Quick Cleaning	Quick clean up the " index system " of the recorded files. 250GB under 2 seconds
Recording Mode	Manual / Timer / Motion / Alarm
Watermark	Yes
Refresh Rate	240 frames per sec. for NTSC / 200 frames per sec. for PAL
Pentaplex Operation	Pentaplex function (live display, recording, playback, backup and network)
Audio I/O	4 audio inputs, 2 audio outputs (Mono)
Motion Detection Area	16 x12 grids per camera
Motion Detect Sensitivity	4 adjustable variables with precise calculation for motion detection
Pre-alarm Recording	Yes
Backup Device	USB 2.0/1.1 backup and through network backup, CD R/W, DVD R/W
R.E.T.R.	Support Remote Event Trigger Recording
Web Transmitting Compression Format	Motion JPEG
Ethernet	10/100 Base-T. Support remote control and live view via Ethernet.
Mobile Surveillance	Support 3G/GPRS to access the system via mobile phone (require J2ME, MIDP2.0 protocol)
Web Interface	Support licensed software AP, and IE browser
Remote Alarm Notification	E-mail images, and images uploading to FTP site's specific account
Network Connection	Support TCP/IP, PPPoE, DHCP and DDNS function
USB Interface	Support 2 USB 1.1 ports (front panel * 1, rear panel * 1)
Remote Control	Remote control DVR and PTZ via IR transmitter
PTZ control	Support PELCO-D protocol
Hot point	Yes
Dwell Time (Sequential Channel Switch)	Programmable with adjustable dwell time
Alarm I/O	8 inputs, 1 output
Picture Zoom	Support 2X digital zoom function
Key Lock	Yes
Video Loss Detection	Yes
Camera Title	Support up to 6 letters
Video Adjustable	Hue / Color / Contrast / Brightness
Date Display Format	YY/MM/DD, DD/MM/YY, MM/DD/YY, and Off
Power Source	DC 19V
Current Consumption	<64 W
Operating Temperature	10 ~ 40 (50 ~104)
Dimensions (mm)	432mm (W) x 90mm (H) x 326mm (D)
System Recovery	System auto recovery after power reconnected
Optional Peripherals	DVD R/W backup or CD R/W backup; Independent Disk Array; VGA output



Evolution for your Demand

Tel:886-2-2655-3866
www.cpcamcctv.com

Fax:886-2-2655-3855
marketing@cpcamcctv.com